CHURCHVILLE GREENE HOMEOWNERS ASSOCIATION, INC. VARIANCE REQUEST

PLEASE RETURN COMPLETED FORM TO:	HOMEO	HOMEOWNER:	
Churchville Greene Homeowners Association			
c/o Realty Performance Group, Inc.	ADDRESS	ADDRESS:	
1800 Hudson Avenue, Suite 100			
Rochester, NY 14617	PHONE	Daytime:	
		Evening:	
TO THE BOARD OF DIRECTORS: I REQUEST PERMISSION TO MAKE THE FOLLOWING CHA AREA OF THE COMMUNITY. I UNDERSTAND THAT IT IS BE NECESSARY FOR THIS WORK. I HAVE ATTACHED A AND INDICATED WHO WILL DO THE WORK (please be ex	MY RESPONSIBILITY SKETCH OF PROPOS	RIOR OF MY TOWNHOUSE OR TO THE COMMON TO OBTAIN ANY BUILDING PERMITS THAT MAY SED CHANGES, LISTED MATERIALS TO BE USED,	
REASON FOR VARIANCE REQUEST:			
WHO WILL COMPLETE THE WORK? (All contractors mustiability and workers compensation insurance): LENGTH OF GUARANTEE (If applicable):			
INDICATE ANY FUTURE MAINTENANCE REQUIRED BY TH	E ASSOCIAITON:		
DATE	SIGNATURE OF PETITOINER		
	========		
BOARD OF DIRECTORS ACTION:API	PROVED	DENIED	
DATE	AUTHORIZED SIGNATURE		
COMMENTS:			
LATEST COMPLETION DATE AFTER WHICH ANY APPROVANCESSARY:	AL IS AUTOMATICAL	LY REVOKED AND NEW VARIANCE REQUEST IS	
DATE ON WHICH ACTED-ON VARIANCE REQUEST MAILEI	O TO PETITIONER		

CHURCHVILLE GREENE HOMEOWNERS ASSOCIATION, INC.

VARIANCE REQUEST CHECKLIST

FENCE:	<u>S:</u>
	On exact footprint and exact dimensions Minimum height 4 feet Maximum height 5 feet Staining must match examples at the barn. Natural wood preservatives only, no paint
WINDO	DWS:
	Slider type (crank or sash windows NOT permitted) Must be exact dimensions Installer specifications and copy of proposal must be included Specify whether all windows will or will not have grids
DOORS	<u>5:</u>
	Must be exact dimensions Installer specifications and copy of proposal must be included Conservative design and color (Must be approved)/Include a picture of door If just painting variance still needed
AIR CO	NDITIONERS:
	Preferred Location – Units should be installed in homeowners patio If not possible must be in current location Installer specifications and copy of proposal must be included Previous openings must be reused
SATELL	ITE DISHES:
	Mounted to fascia area on "stand-off" brackets Wire should enter at closest point Wire concealed behind the J Channel or corner piece to prevent hanging
OTHER	<u>:</u>
	Modifications must be per Declaration and policy of the Association, and must be approved by the Board BEFORE beginning work
Signatı	ure of Homeowner Date

CHURCHVILLE GREENE HOMEOWNERS ASSOCIATION, INC.

VARIANCE SPECIFICATIONS

FENCES: The stockade fence should be no higher than five feet above the ground at any point. The top of the fence must be level. The length of the slats should be no less than four feet but no more than five feet (pressure-treated lumber may be used). The replacement fence must be the exact dimensions / footprint of the original fence. **The Underground Detection Service** must be called for a utility stake out prior to any excavation, **1-800-962-7962.**

FENCE STAINING: Only natural wood preservatives are to be used. Samples of these preservative are on display at the barn. **Paint is not acceptable.**

<u>REPLACEMENT WINDOWS / DOORS</u>: Windows must be identical in kind. Windows must be slider windows (crank or sash windows are not permitted). Upgraded materials may be permitted. Variance must include a copy of the installer's specifications along with a copy of the proposal from the installer.

<u>AIR CONDITIONERS</u>: If possible, air conditioning units must be installed in the homeowner's enclosed patio. Any previous holes from lines into the unit from the air conditioning unit to be replaced must be reused. Variance is to include a copy of the installer's specifications along with a copy of the proposal from the installer.

<u>SATELLITE DISHES</u>: All satellite dishes are to be professionally installed and are to include copies of the installer's specifications and proposal. The Board of Directors will designate the location. Mounting of "super dish" sized satellite dish will be on the fascia, roof mounting will not be permitted. Location will be noted on variance request.

ROOF VENTS: (Added 09/10/97) Any type of roof vents installed by owner / contractor must match existing vents on roof where vent is to be installed (or as close as possible). Any damage to roofs and/or units during the installation of the vent will be the homeowner's responsibility to repair / replace to the condition prior to damage. All work is to be guaranteed for two (2) years.

OTHER: Modifications must be per Declaration and policy of the Association and must be approved by Association Board **BEFORE** beginning work.